

ROADX

RXQUEST AT QX12



PREMIUM ALL TERRAIN

The RoadX RXQuest AT QX12 is the perfect all-terrain (A/T) tire for light truck, SUV and crossover drivers. The advanced tread pattern and aggressive sidewall allow it to handle all you can throw at it both on-and-off road terrains. This A/T tire is built to last while also providing a smooth and quiet ride for cruising. The wide shoulders provide excellent grip in wet conditions and the rim protector allows you to take on any trail with confidence in knowing that your wheels have that extra level of protection against the elements.

FEATURES & BENEFITS

CONTROL

- Optimized contact patch for maximum traction and stability.

TRUSTED GRIP

- Aggressive shoulder design increasing off-road bite and providing extra protection.

BALANCED TRACTION

- Aggressive shoulder design increasing off-road bite and providing extra protection.
- 3PMS certified

Le RoadX RXQuest AT QX12 est le pneu tout terrain (A/T) idéal pour les camionnettes, les VUS et les multiségments. Le dessin de la bande de roulement évolué et les flancs dynamiques lui permettent d'affronter tous les types de terrains pour une conduite hors route et sur la route. Ce pneu A/T est conçu pour durer tout en offrant une conduite silencieuse et en douceur. L'épaule large procure une excellente adhérence dans des conditions mouillées, et le protecteur de jante vous permet d'emprunter n'importe quel sentier avec confiance en sachant que vos roues bénéficient d'une protection supplémentaire contre les éléments.

CARACTÉRISTIQUES

CONTRÔLE

- L'empreinte au sol est optimisée pour offrir une adhérence et une stabilité maximales.

ADHÉRENCE DE CONFIANCE


- La conception d'épaule dynamique améliore l'adhérence hors route et offre une protection supplémentaire.

TRACTION ÉQUILIBRÉE

- Le pavé présente une conception de style escalier réduisant la rétention de cailloux et le bruit de la route.
- Homologation 3PMS



PERFORMANCE RATINGS:



R, S, T SPEED RATED
UTQG 600 A B

ROADX**RXQUEST AT QX12** 

PART NUMBER	SIZE	LI/SR	TD 32/IN.	OD IN.	SW IN.	RW IN.	UTQG	SINGLE MAX LOAD LBS@PSI	DUAL MAX LOAD LBS@PSI
1600092K	235/75R15	109S	13	28.9	9.3	6.5	600 A B	2271@50	
1600088K	235/70R16	106S	13	29.0	9.5	7.0	600 A B	2094@44	
1600095K	245/75R16	111S	13	30.5	9.8	7.0	600 A B	2403@44	
1600099K	265/70R16	112T	13	30.6	10.7	8.0	600 A B	2469@44	
1600101K	265/75R16	116S	13	31.7	10.5	7.5	600 A B	2756@44	
1602169K	225/60R17	99T	13	27.6	9.0	6.5	600 A B	1709@44	
1602170K	225/65R17	106T	13	28.5	9.0	6.5	600 A B	2094@50	
1600087K	235/65R17	104S	13	29.1	9.5	7.0	600 A B	1984@44	
1600093K	245/65R17	107S	13	29.5	9.8	7.0	600 A B	2149@44	
1600094K	245/70R17	110T	13	30.6	9.8	7.0	600 A B	2337@44	
1600097K	265/65R17	112S	13	30.6	10.7	8.0	600 A B	2469@44	
1600100K	265/70R17	115S	13	31.7	10.7	8.0	600 A B	2679@44	
1602171K	235/60R18	107T	13	29.1	9.5	7.0	600 A B	2149@50	
1600098K	265/65R18	114T	13	31.5	10.7	8.0	600 A B	2601@44	
1600090K	275/65R18	116T	13	32.1	11.0	8.0	600 A B	2756@44	
1600096K	265/50R20	111T	13	30.5	10.9	8.5	600 A B	2403@50	
1600121K	275/55R20	117T	13	31.9	11.2	8.5	600 A B	2833@50	
1600089K	275/60R20	115T	13	33.0	11.0	8.0	600 A B	2679@44	
1602172K	275/50R22	115T	13	32.8	11.1	8.5	600 A B	2679@50	
1602126K	285/45R22	114H	13	32.1	11.2	9.5	600 A B	2601@50	
1600104K	LT235/75R15	104/101R	16	28.9	9.3	6.5		1985@50	1820@50
1600103K	LT225/75R16	115/112S	16	29.3	8.8	6.0		2680@80	2470@80
1600106K	LT235/85R16	120/116S	16	31.7	9.3	6.5		3042@80	2778@80
1600108K	LT245/75R16	120/116S	16	30.5	9.8	7.0		3042@80	2778@80
1600113K	LT265/75R16	123/120S	16	31.7	10.5	7.5		3415@80	3085@80
1600119K	LT285/75R16	126/123S	16	33.1	11.3	8.0		3750@80	3415@80
1600105K	LT235/80R17	120/117R	16	31.8	9.3	6.5		3085@80	2835@80
1600107K	LT245/70R17	119/116S	16	30.6	9.8	7.0		3000@80	2755@80
1600109K	LT245/75R17	121/118S	16	31.5	9.8	7.0		3195@80	2910@80
1600111K	LT265/70R17	121/118S	16	31.7	10.7	8.0		3195@80	2910@80
1600118K	LT285/70R17	121/118S	16	32.8	11.5	8.5		3195@80	2910@80
1600112K	LT265/70R18	124/121R	16	32.6	10.7	8.0		3525@80	3195@80
1600116K	LT275/65R18	123/120S	16	32.1	11.0	8.0		3415@80	3085@80
1600117K	LT275/70R18	125/122R	16	33.2	11.0	8.0		3640@80	3305@80
1600110K	LT265/60R20	121/118R	16	32.5	10.7	8.0		3195@80	2910@80
1605104K	LT275/55R20	120/117R	16	31.9	11.2	8.5		2680@65	2470@65
1600115K	LT275/60R20	123/120R	16	33.0	11.0	8.0		3415@80	3085@80
1600102K	LT275/65R20	126/123S	16	34.1	11.0	8.0		3750@80	3415@80
1600120K	LT305/55R20	121/118R	16	33.2	12.4	9.5		3195@65	2910@65
1602173K	LT315/70R17	126/123S	16	34.4	12.7	9.5		3750@65	3415@65
1600091K	31X10.50R15LT	109S	16	30.5	10.6	8.5		2270@50	
1602174K	33X12.50R20LT	114S	16	33.0	12.5	10		2600@65	
1602127K	35X12.50R20LT	121R	16	35.0	12.5	10		3195@65	